

## steel or aluminum

**Crossover Bridges** 

Easy, convenient access over obstacles

COTTERMAN® CROSSOVER BRIDGES provide safe walkways over a variety of obstacles such as conveyors, machines, and pipes.

- 500 lb. load rating.
- 50° climb angle, with 8" step rise.
- 42" high guardrails.
- Stair sections have 24<sup>1</sup>/<sub>8</sub>" wide x 7" deep steps. The top platform includes a 4" high toe board on each side.
- Legs have floor mounting plate with 5/8" diameter hole.
- · Serrated or Diamond Plate steps.
- Ships unassembled.
- Gray powder coat finish is standard on steel models. Aluminum is a brightened, uniform finish.
- Crossover Bridges meet applicable OSHA and ANSI standards.



## Crossover bridges model numbers & measurements

LOAD RATING **500 LBS.** 

MADE IN U.S.A.

NO. OF STEPS	PLATFORM HEIGHT	OVERALL HEIGHT	STANDING HEIGHT (approx.)	STEP WIDTH	BASE WIDTH	24" PLATFORM DEPTH					36" PLATFORM DEPTH				
						MODEL Number	OVERALL LENGTH	CLEAR HT.	CLEAR WIDTH	SHP. WT. LBS.	MODEL Number	OVERALL LENGTH	CLEAR HT.	CLEAR WIDTH	SHP. WT. LBS.
STEEL															
4 STEP	32"	74"	104"	24"	28%"	4SCS24A3	86"	30"	24%"	328	4SCS36A3	98"	30"	36%"	359
5 STEP	40"	82"	112"	24"	28%"	5SCS24A3	99"	38"	24%"	371	5SCS36A3	111"	38"	36%"	401
6 STEP	48"	90"	120"	24"	28%"	6SCS24A3	113"	46"	24%"	413	6SCS36A3	125"	46"	36%"	444
7 STEP	56"	98"	128"	24"	28%"	7SCS24A3	126"	54"	24%"	456	7SCS36A3	138"	54"	36%"	486
ALUMINUM															
4 STEP	32"	74"	104"	24"	28%"	4SCA24A3	86"	30"	24%"	158	4SCA36A3	98"	30"	36%"	170
5 STEP	40"	82"	112"	24"	28%"	5SCA24A3	99"	38"	24%"	175	5SCA36A3	111"	38"	36%"	188
6 STEP	48"	90"	120"	24"	28%"	6SCA24A3	113"	46"	24%"	193	6SCA36A3	125"	46"	36%"	205
7 STEP	56"	98"	128"	24"	28%"	7SCA24A3	126"	54"	24%"	210	7SCA36A3	138"	54"	36%"	222

 ${\bf NUMBER\ OF\ STEPS\ IS\ THE\ NUMBER\ OF\ STEPS\ ON\ EACH\ SIDE,\ INCLUDING\ PLATFORM.}$