

SPACE SAVER Crossover Bridges



COTTERMAN® SPACE-SAVER CROSSOVER BRIDGES provide safe access over obstacles in areas with limited space due to a steeper climb angle.

- 500 lb. load rating.
- 70° climb angle, with 8" step rise.
- 42" Handrails, constructed of 1½" diameter round tube.
- Stair sections have 24¹/₈" wide x 4⁷/₈" deep steps. The top platform includes a 4" high toe board on each side.
- Legs have floor mounting plate with 5/8" diameter hole.
- Serrated or Diamond Plate steps.
- Ships unassembled.
- Gray powder coat finish is standard on steel models. Aluminum is a brightened, uniform finish.
- Cal-OSHA requires customers to request a variance for specific application.

NOTE: Before erecting Space Saver Crossover Bridge, check federal, state and local codes.

Space-Saver Crossover Bridges MODEL NUMBERS & MEASUREMENTS

**LOAD RATING
500 LBS.**

NO. OF STEPS	PLATFORM HEIGHT	OVERALL HEIGHT	STANDING HEIGHT (approx.)	STEP WIDTH	BASE WIDTH	24" PLATFORM DEPTH				36" PLATFORM DEPTH					
						MODEL NUMBER	OVERALL LENGTH	CLEAR HT.	CLEAR LGTH.	WEIGHT LBS.	MODEL NUMBER	OVERALL LENGTH	CLEAR HT.	CLEAR LGTH.	WEIGHT LBS.
STEEL															
4 STEP	32"	74"	104"	24"	28 ⁵ / ₈ "	4SPS24A3	55"	30"	25 ⁹ / ₁₆ "	245	4SPS36A3	67"	30"	37 ⁹ / ₁₆ "	276
5 STEP	40"	82"	112"	24"	28 ⁵ / ₈ "	5SPS24A3	61"	38"	25 ⁹ / ₁₆ "	273	5SPS36A3	73"	38"	37 ⁹ / ₁₆ "	303
6 STEP	48"	90"	120"	24"	28 ⁵ / ₈ "	6SPS24A3	67"	46"	25 ⁹ / ₁₆ "	300	6SPS36A3	78"	46"	37 ⁹ / ₁₆ "	330
7 STEP	56"	98"	128"	24"	28 ⁵ / ₈ "	7SPS24A3	73"	54"	25 ⁹ / ₁₆ "	327	7SPS36A3	84"	54"	37 ⁹ / ₁₆ "	358
ALUMINUM															
4 STEP	32"	74"	104"	24"	28 ⁵ / ₈ "	4SPA24A3	55"	30"	25 ⁹ / ₁₆ "	123	4SPA36A3	67"	30"	37 ⁹ / ₁₆ "	135
5 STEP	40"	82"	112"	24"	28 ⁵ / ₈ "	5SPA24A3	61"	38"	25 ⁹ / ₁₆ "	133	5SPA36A3	73"	38"	37 ⁹ / ₁₆ "	145
6 STEP	48"	90"	120"	24"	28 ⁵ / ₈ "	6SPA24A3	67"	46"	25 ⁹ / ₁₆ "	143	6SPA36A3	78"	46"	37 ⁹ / ₁₆ "	155
7 STEP	56"	98"	128"	24"	28 ⁵ / ₈ "	7SPA24A3	73"	54"	25 ⁹ / ₁₆ "	153	7SPA36A3	84"	54"	37 ⁹ / ₁₆ "	165

